

ZODZ.E157233 - Positioning Devices

Positioning Devices

[See General Information for Positioning Devices](#)

BAND-IT-IDEX INC
 4799 Dahlia St
 Denver, CO 80216 USA

E157233

Band-Fast Un-Coated Metallic Cable Ties Investigated to ANSI/UL 62275

Cat. No.	Type Dsg.	Bundle Diam., mm(in.)		Loop Tensile Str., N(lbf)	Operating Temp., °C(°F)		Resistant to UV Light	Plenum Rating	Also Classified to [^] IEC 62275 and EN 62275
		Min	Max		Min	Max			
L203	2	19 (0.75)	51 (2.01)	2001 (450)	-60 (-76)	300 (572)	Yes	AH-1	-
L204	2	19 (0.75)	89 (3.50)	2001 (450)	-60 (-76)	300 (572)	Yes	AH-1	-
L207	2	19 (0.75)	127 (5.00)	2001 (450)	-60 (-76)	300 (572)	Yes	AH-1	-
L208	2	19 (0.75)	178 (7.01)	2001 (450)	-60 (-76)	300 (572)	Yes	AH-1	-
L210	2	19 (0.75)	229 (9.02)	2001 (450)	-60 (-76)	300 (572)	Yes	AH-1	-
L221	2	25.4 (1.00)	89 (3.50)	4003 (900)	-60 (-76)	300 (572)	Yes	AH-1	-
L229	2	25.4 (1.00)	305 (12.01)	4003 (900)	-60 (-76)	300 (572)	Yes	AH-1	-
L284	2	32 (1.26)	152 (5.98)	8896 (2000)	-60 (-76)	300 (572)	Yes	AH-1	-
L288	2	32 (1.26)	254 (10.00)	8896 (2000)	-60 (-76)	300 (572)	Yes	AH-1	-
L290	2	32 (1.26)	356 (14.02)	8896 (2000)	-60 (-76)	300 (572)	Yes	AH-1	-
L292	2	32 (1.26)	457 (17.99)	8896 (2000)	-60 (-76)	300 (572)	Yes	AH-1	-

Band-IT Coated Metallic Cable Ties Investigated to ANSI/UL 62275

Cat. No.	Type Dsg.	Bundle Diam., mm(in.)		Loop Tensile Str., N(lbf)	Operating Temp., °C(°F)		Resistant to UV Light	Plenum Rating	Also Classified to [^] IEC 62275 and EN 62275
		Min	Max		Min	Max			
		AE111	21		31.75 (1.25)	38.1 (1.50)			
AE112	21	31.75 (1.25)	63.5 (2.50)	334 (75)	-40 (-40)	150 (302)	Yes	-	-
AE113	21	31.75 (1.25)	86.4 (3.40)	334 (75)	-40 (-40)	150 (302)	Yes	-	-
AE114	21	31.75 (1.25)	137.2 (5.40)	334 (75)	-40 (-40)	150 (302)	Yes	-	-
AE115	21	31.75 (1.25)	185.4 (7.30)	334 (75)	-40 (-40)	150 (302)	Yes	-	-
AE311	21	31.75 (1.25)	38.1 (1.50)	445 (100)	-40 (-40)	150 (302)	Yes	-	-
AE312	21	31.75 (1.25)	63.5 (2.50)	445 (100)	-40 (-40)	150 (302)	Yes	-	-
AE313	21	31.75 (1.25)	86.4 (3.40)	445 (100)	-40 (-40)	150 (302)	Yes	-	-
AE314	21	31.75 (1.25)	137.2 (5.40)	445 (100)	-40 (-40)	150 (302)	Yes	-	-
AE315	21	31.75 (1.25)	185.4 (7.30)	445 (100)	-40 (-40)	150 (302)	Yes	-	-
AE316	21	31.75 (1.25)	231.1 (9.10)	445 (100)	-40 (-40)	150 (302)	Yes	-	-
AE317	21	31.75 (1.25)	279.4 (11.00)	445 (100)	-40 (-40)	150 (302)	Yes	-	-

Coated Metallic Cable Ties Investigated to ANSI/UL 62275

Cat. No.	Type Dsg.	Bundle Diam., mm(in.)		Loop Tensile Str., N(lbf)	Operating Temp., °C(°F)		Resistant to UV Light	Plenum Rating	Also Classified to [^] IEC 62275 and EN 62275
		Min	Max		Min	Max			
		KT4B046-0100	2		12.7 (0.50)	25 (0.98)			
KT4B046-0150	2	12.7 (0.50)	37 (1.46)	710 (160)	-40 (-40)	150 (302)	Yes	-	-
KT4B046-0200	2	12.7 (0.50)	50 (1.97)	710 (160)	-40 (-40)	150 (302)	Yes	-	-

KT4B046-0250	2	12.7 (0.50)	63 (2.48)	710 (160)	-40 (-40)	150 (302)	Yes	-	-
KT4B046-0300	2	12.7 (0.50)	76 (2.99)	710 (160)	-40 (-40)	150 (302)	Yes	-	-
KT4B046-0350	2	12.7 (0.50)	89 (3.50)	710 (160)	-40 (-40)	150 (302)	Yes	-	-
KT4B046-0400	2	12.7 (0.50)	102 (4.02)	710 (160)	-40 (-40)	150 (302)	Yes	-	-
KT4B046-0450	2	12.7 (0.50)	115 (4.53)	710 (160)	-40 (-40)	150 (302)	Yes	-	-
KT4B046-0500	2	12.7 (0.50)	128 (5.04)	710 (160)	-40 (-40)	150 (302)	Yes	-	-
KT4B078-0150	2	12.7 (0.50)	37 (1.46)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-
KT4B078-0200	2	12.7 (0.50)	50 (1.97)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-
KT4B078-0250	2	12.7 (0.50)	63 (2.48)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-
KT4B078-0300	2	12.7 (0.50)	76 (2.99)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-
KT4B078-0350	2	12.7 (0.50)	89 (3.50)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-
KT4B078-0400	2	12.7 (0.50)	102 (4.02)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-
KT4B078-0450	2	12.7 (0.50)	115 (4.53)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-
KT4B078-0500	2	12.7 (0.50)	128 (5.04)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-
KT4B078-0550	2	12.7 (0.50)	141 (5.55)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-
KT4B078-0600	2	12.7 (0.50)	154 (6.06)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-
KT4B120-0150	2	25.4 (1.00)	50 (1.97)	2000 (450)	-40 (-40)	150 (302)	Yes	-	-
KT4B120-0200	2	25.4 (1.00)	63 (2.48)	2000 (450)	-40 (-40)	150 (302)	Yes	-	-
KT4B120-0250	2	25.4 (1.00)	76 (2.99)	2000 (450)	-40 (-40)	150 (302)	Yes	-	-
KT4B120-0300	2	25.4 (1.00)	89 (3.50)	2000 (450)	-40 (-40)	150 (302)	Yes	-	-

KT4B120-0350	2	25.4 (1.00)	102 (4.02)	2000 (450)	-40 (-40)	150 (302)	Yes	-	-
KT4B120-0400	2	25.4 (1.00)	115 (4.53)	2000 (450)	-40 (-40)	150 (302)	Yes	-	-
KT4B120-0450	2	25.4 (1.00)	128 (5.04)	2000 (450)	-40 (-40)	150 (302)	Yes	-	-
KT4B120-0500	2	25.4 (1.00)	141 (5.55)	2000 (450)	-40 (-40)	150 (302)	Yes	-	-
KT4B120-0550	2	25.4 (1.00)	154 (6.06)	2000 (450)	-40 (-40)	150 (302)	Yes	-	-
KT4B120-0600	2	25.4 (1.00)	167 (6.57)	2000 (450)	-40 (-40)	150 (302)	Yes	-	-
KT4B150-0150	2	25.4 (1.00)	76 (2.99)	3000 (674)	-40 (-40)	150 (302)	Yes	-	-
KT4B150-0200	2	25.4 (1.00)	89 (3.50)	3000 (674)	-40 (-40)	150 (302)	Yes	-	-
KT4B150-0250	2	25.4 (1.00)	102 (4.02)	3000 (674)	-40 (-40)	150 (302)	Yes	-	-
KT4B150-0300	2	25.4 (1.00)	115 (4.53)	3000 (674)	-40 (-40)	150 (302)	Yes	-	-
KT4B150-0350	2	25.4 (1.00)	128 (5.04)	3000 (674)	-40 (-40)	150 (302)	Yes	-	-
KT4B150-0400	2	25.4 (1.00)	141 (5.55)	3000 (674)	-40 (-40)	150 (302)	Yes	-	-
KT4B150-0450	2	25.4 (1.00)	154 (6.06)	3000 (674)	-40 (-40)	150 (302)	Yes	-	-
KT4B150-0500	2	25.4 (1.00)	167 (6.57)	3000 (674)	-40 (-40)	150 (302)	Yes	-	-
KT4B150-0550	2	25.4 (1.00)	180 (7.09)	3000 (674)	-40 (-40)	150 (302)	Yes	-	-
KT4B150-0600	2	25.4 (1.00)	193 (7.60)	3000 (674)	-40 (-40)	150 (302)	Yes	-	-

Epoxy Coated-Metallic Cable Ties Investigated to ANSI/UL 62275

Cat. No.	Type Dsg.	Bundle Diam., mm(in.)		Loop Tensile Str., N(lbf)	Operating Temp., °C(°F)		Resistant to UV Light	Plenum Rating	Also Classified to
		Min	Max		Min	Max			[^]
									IEC 62275 and EN 62275
KE02AAUK*	21	20 (0.79)	30-305 (1.18)	667 (150)	-40 (-40)	150 (302)	Yes	AH-2	-

KE04BBUK*	21	20 (0.79)	51-305 (2.01)	778 (175)	-40 (-40)	150 (302)	Yes	AH-2	-
XE02AAUK*	21	20 (0.79)	30-305 (1.18)	667 (150)	-40 (-40)	150 (302)	Yes	AH-2	-
XE04AAUK*	21	20 (0.79)	30-305 (1.18)	778 (175)	-40 (-40)	150 (302)	Yes	AH-2	-

Metallic Cable Ties Investigated to ANSI/UL 62275

Cat. No.	Type Dsg.	Bundle Diam., mm(in.)		Loop Tensile Str., N(lbf)	Operating Temp., °C(°F)		Resistant to UV Light	Plenum Rating	Also Classified to [^] IEC 62275 and EN 62275
		Min	Max		Min	Max			
		KT4U046-0100	2		12.7 (0.50)	25 (0.98)			
KT4U046-0150	2	12.7 (0.50)	37 (1.46)	1000 (225)	-60 (-76)	300 (572)	Yes	-	-
KT4U046-0200	2	12.7 (0.50)	50 (1.97)	1000 (225)	-60 (-76)	300 (572)	Yes	-	-
KT4U046-0250	2	12.7 (0.50)	63 (2.48)	1000 (225)	-60 (-76)	300 (572)	Yes	-	-
KT4U046-0300	2	12.7 (0.50)	76 (2.99)	1000 (225)	-60 (-76)	300 (572)	Yes	-	-
KT4U046-0350	2	12.7 (0.50)	89 (3.50)	1000 (225)	-60 (-76)	300 (572)	Yes	-	-
KT4U046-0400	2	12.7 (0.50)	102 (4.02)	1000 (225)	-60 (-76)	300 (572)	Yes	-	-
KT4U046-0450	2	12.7 (0.50)	115 (4.53)	1000 (225)	-60 (-76)	300 (572)	Yes	-	-
KT4U046-0500	2	12.7 (0.50)	128 (5.04)	1000 (225)	-60 (-76)	300 (572)	Yes	-	-
KT4U078-0150	2	12.7 (0.50)	50 (1.97)	2220 (499)	-60 (-76)	300 (572)	Yes	-	-
KT4U078-0200	2	12.7 (0.50)	63 (2.48)	2220 (499)	-60 (-76)	300 (572)	Yes	-	-
KT4U078-0250	2	12.7 (0.50)	76 (2.99)	2220 (499)	-60 (-76)	300 (572)	Yes	-	-
KT4U078-0300	2	12.7 (0.50)	89 (3.50)	2220 (499)	-60 (-76)	300 (572)	Yes	-	-
KT4U078-0350	2	12.7 (0.50)	102 (4.02)	2220 (499)	-60 (-76)	300 (572)	Yes	-	-

KT4U078-0400	2	12.7 (0.50)	115 (4.53)	2220 (499)	-60 (-76)	300 (572)	Yes	-	-
KT4U078-0450	2	12.7 (0.50)	128 (5.04)	2220 (499)	-60 (-76)	300 (572)	Yes	-	-
KT4U078-0500	2	12.7 (0.50)	141 (5.55)	2220 (499)	-60 (-76)	300 (572)	Yes	-	-
KT4U078-0550	2	12.7 (0.50)	154 (6.06)	2220 (499)	-60 (-76)	300 (572)	Yes	-	-
KT4U078-0600	2	12.7 (0.50)	167 (6.57)	2220 (499)	-60 (-76)	300 (572)	Yes	-	-
KT4U120-0150	2	25.4 (1.00)	50 (1.97)	3115 (700)	-60 (-76)	300 (572)	Yes	-	-
KT4U120-0200	2	25.4 (1.00)	63 (2.48)	3115 (700)	-60 (-76)	300 (572)	Yes	-	-
KT4U120-0250	2	25.4 (1.00)	76 (2.99)	3115 (700)	-60 (-76)	300 (572)	Yes	-	-
KT4U120-0300	2	25.4 (1.00)	89 (3.50)	3115 (700)	-60 (-76)	300 (572)	Yes	-	-
KT4U120-0350	2	25.4 (1.00)	102 (4.02)	3115 (700)	-60 (-76)	300 (572)	Yes	-	-
KT4U120-0400	2	25.4 (1.00)	115 (4.53)	3115 (700)	-60 (-76)	300 (572)	Yes	-	-
KT4U120-0450	2	25.4 (1.00)	128 (5.04)	3115 (700)	-60 (-76)	300 (572)	Yes	-	-
KT4U120-0500	2	25.4 (1.00)	141 (5.55)	3115 (700)	-60 (-76)	300 (572)	Yes	-	-
KT4U120-0550	2	25.4 (1.00)	154 (6.06)	3115 (700)	-60 (-76)	300 (572)	Yes	-	-
KT4U120-0600	2	25.4 (1.00)	167 (6.57)	3115 (700)	-60 (-76)	300 (572)	Yes	-	-
KT4U150-0150	2	25.4 (1.00)	76 (2.99)	4100 (922)	-60 (-76)	300 (572)	Yes	-	-
KT4U150-0200	2	25.4 (1.00)	89 (3.50)	4100 (922)	-60 (-76)	300 (572)	Yes	-	-
KT4U150-0250	2	25.4 (1.00)	102 (4.02)	4100 (922)	-60 (-76)	300 (572)	Yes	-	-
KT4U150-0300	2	25.4 (1.00)	115 (4.53)	4100 (922)	-60 (-76)	300 (572)	Yes	-	-
KT4U150-0350	2	25.4 (1.00)	128 (5.04)	4100 (922)	-60 (-76)	300 (572)	Yes	-	-

KT4U150-0400	2	25.4 (1.00)	141 (5.55)	4100 (922)	-60 (-76)	300 (572)	Yes	-	-
KT4U150-0450	2	25.4 (1.00)	154 (6.06)	4100 (922)	-60 (-76)	300 (572)	Yes	-	-
KT4U150-0500	2	25.4 (1.00)	167 (6.57)	4100 (922)	-60 (-76)	300 (572)	Yes	-	-
KT4U150-0550	2	25.4 (1.00)	180 (7.09)	4100 (922)	-60 (-76)	300 (572)	Yes	-	-
KT4U150-0600	2	25.4 (1.00)	193 (7.60)	4100 (922)	-60 (-76)	300 (572)	Yes	-	-

Multi-Lok Coated Metallic Cable Ties Investigated to ANSI/UL 62275

Cat. No.	Type Dsg.	Bundle Diam., mm(in.)		Loop Tensile Str., N(lbf)	Operating Temp., °C(°F)		Resistant to UV Light	Plenum Rating	Also Classified to [^] IEC 62275 and EN 62275
		Min	Max		Min	Max			
		AE611	21		19 (0.75)	33.0 (1.30)			
AE612	21	19 (0.75)	55.9 (2.20)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-
AE613	21	19 (0.75)	81.3 (3.20)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-
AE614	21	19 (0.75)	130.0 (5.12)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-
AE615	21	19 (0.75)	180.3 (7.10)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-
AE711	21	19 (0.75)	33.0 (1.30)	1846 (415)	-40 (-40)	150 (302)	Yes	AH-2	-
AE712	21	19 (0.75)	55.9 (2.20)	1846 (415)	-40 (-40)	150 (302)	Yes	AH-2	-
AE713	21	19 (0.75)	81.3 (3.20)	1846 (415)	-40 (-40)	150 (302)	Yes	AH-2	-
AE714	21	19 (0.75)	130.0 (5.12)	1846 (415)	-40 (-40)	150 (302)	Yes	AH-2	-
AE715	21	19 (0.75)	180.3 (7.10)	1846 (415)	-40 (-40)	150 (302)	Yes	AH-2	-

Multi-Lok Un-Coated Metallic Cable Ties Investigated to ANSI/UL 62275

Cat. No.	Type Dsg.	Bundle Diam., mm(in.)	Loop Tensile Str., N(lbf)	Operating Temp., °C(°F)	Resistant to UV Light	Plenum Rating	Also Classified to [^] IEC 62275 and EN 62275
----------	-----------	-----------------------	---------------------------	-------------------------	-----------------------	---------------	-----------------------------------------------

		Min	Max		Min	Max			
AE601	2	19 (0.75)	33 (1.30)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
AE602	2	19 (0.75)	56 (2.20)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
AE603	2	19 (0.75)	81 (3.19)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
AE604	2	19 (0.75)	130 (5.12)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
AE605	2	19 (0.75)	180 (7.09)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
AE701	2	19 (0.75)	33 (1.30)	1846 (415)	-60 (-76)	300 (572)	Yes	AH-1	-
AE702	2	19 (0.75)	56 (2.20)	1846 (415)	-60 (-76)	300 (572)	Yes	AH-1	-
AE703	2	19 (0.75)	81 (3.19)	1846 (415)	-60 (-76)	300 (572)	Yes	AH-1	-
AE704	2	19 (0.75)	130 (5.12)	1846 (415)	-60 (-76)	300 (572)	Yes	AH-1	-
AE705	2	19 (0.75)	180 (7.09)	1846 (415)	-60 (-76)	300 (572)	Yes	AH-1	-
TB601	2	19 (0.75)	33 (1.30)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
TB602	2	19 (0.75)	56 (2.20)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
TB603	2	19 (0.75)	81 (3.19)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
TB604	2	19 (0.75)	130 (5.12)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
TB605	2	19 (0.75)	180 (7.09)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
TB701	2	19 (0.75)	33 (1.30)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
TB702	2	19 (0.75)	56 (2.20)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
TB703	2	19 (0.75)	81 (3.19)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
TB704	2	19 (0.75)	130 (5.12)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-

TB705	2	19 (0.75)	180 (7.09)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
--------------	---	--------------	---------------	------------	--------------	--------------	-----	------	---

Nylon Coated-Metallic Cable Ties Investigated to ANSI/UL 62275

Cat. No.	Type Dsg.	Bundle Diam., mm(in.)		Loop Tensile Str., N(lbf)	Operating Temp., °C(°F)		Resistant to UV Light	Plenum Rating	Also Classified to [^] IEC 62275 and EN 62275
		Min	Max		Min	Max			
		KE06AA*	21		20 (0.79)	30-254 (1.18)			
KE08AA*	21	20 (0.79)	30-254 (1.18)	533 (120)	-40 (-40)	140 (284)	Yes	AH-2	-

S.I.D. Tie-Lok Un-Coated Metallic Cable Ties Investigated to ANSI/UL 62275

Cat. No.	Type Dsg.	Bundle Diam., mm(in.)		Loop Tensile Str., N(lbf)	Operating Temp., °C(°F)		Resistant to UV Light	Plenum Rating	Also Classified to [^] IEC 62275 and EN 62275
		Min	Max		Min	Max			
		AS211	2		12.7 (0.50)	50.8 (2.00)			
AS212	2	12.7 (0.50)	102 (4.02)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
AS213	2	12.7 (0.50)	152 (5.98)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
AS214	2	12.7 (0.50)	203 (7.99)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
AS215	2	12.7 (0.50)	254 (10.00)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
AS221	2	12.7 (0.50)	25.4 (1.00)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1	-
AS222	2	12.7 (0.50)	50.8 (2.00)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1	-
AS223	2	12.7 (0.50)	102 (4.02)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1	-
AS224	2	12.7 (0.50)	152 (5.98)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1	-
AS225	2	12.7 (0.50)	203 (7.99)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1	-
AS411	2	12.7 (0.50)	50.8 (2.00)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-

AS412	2	12.7 (0.50)	102 (4.02)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
AS413	2	12.7 (0.50)	152 (5.98)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
AS414	2	12.7 (0.50)	203 (7.99)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
AS415	2	12.7 (0.50)	254 (10.00)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
AS421	2	12.7 (0.50)	25.4 (1.00)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1	-
AS422	2	12.7 (0.50)	50.8 (2.00)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1	-
AS423	2	12.7 (0.50)	102 (4.02)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1	-
AS424	2	12.7 (0.50)	152 (5.98)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1	-
AS425	2	12.7 (0.50)	203 (7.99)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1	-

Un-Coated Metallic Cable Ties Investigated to ANSI/UL 62275

Cat. No.	Type Dsg.	Bundle Diam., mm(in.)		Loop Tensile Str., N(lbf)	Operating Temp., °C(°F)		Resistant to UV Light	Plenum Rating	Also Classified to [^] IEC 62275 and EN 62275
		Min	Max		Min	Max			
KE01AAUK*	2	20 (0.79)	30-305 (1.18)	890 (200)	-60 (-76)	300 (572)	Yes	AH-1	-
KE03AAUK*	2	20 (0.79)	30-305 (1.18)	1334 (300)	-60 (-76)	300 (572)	Yes	AH-1	-
KE11AAUK*	2	20 (0.79)	30-305 (1.18)	890 (200)	-60 (-76)	300 (572)	Yes	AH-1	-
KE13AAUK*	2	20 (0.79)	30-338 (1.18)	1334 (300)	-60 (-76)	300 (572)	Yes	AH-1	-
XE01AAUK*	2	20 (0.79)	30-305 (1.18)	890 (200)	-60 (-76)	300 (572)	Yes	AH-1	-
XE03AAUK*	2	20 (0.79)	30-305 (1.18)	1334 (300)	-60 (-76)	300 (572)	Yes	AH-1	-
XE11AAUK*	2	20 (0.79)	30-305 (1.18)	890 (200)	-60 (-76)	300 (572)	Yes	AH-1	-
XE13AAUK*	2	20 (0.79)	30-338 (1.18)	1334 (300)	-60 (-76)	300 (572)	Yes	AH-1	-

* - The letters within the designation are replaced by numeric digits that correspond to the manufacturer's specific strap length: AA represents 18 to 88, BB represents 28 to 88.

Note - All cable ties designations may include an alphanumeric suffix related to packaging requirements and quantity.

Last Updated on 2019-09-27

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2022 UL LLC"