

# ZODZ7.E157233 - POSITIONING DEVICES CERTIFIED FOR CANADA

## Positioning Devices Certified for Canada

See General Information for Positioning Devices Certified for Canada

**BAND-IT-IDEX INC**

E157233


4799 Dahlia St  
Denver, CO 80216 USA

### Band-Fast Un-Coated Metallic Cable Ties Investigated to CAN/CSA-C22.2 No. 62275

Cat. No.	Type Dsg.	Bundle Diam., mm(in.)		Loop Tensile Str., N(lbf)	Operating Temp., °C(°F)		Resistant to UV Light	Plenum Rating	Also Classified to [^] IEC 62275 and EN 62275
		Min	Max		Min	Max			
L221+	2	25.4 (1.00)	89 (3.50)	4003 (900)	-60 (-76)	300 (572)	Yes	AH-1	-
L229+	2	25.4 (1.00)	305 (12.01)	4003 (900)	-60 (-76)	300 (572)	Yes	AH-1	-
L242+	2	32 (1.26)	102 (4.02)	6227 (1400)	-60 (-76)	300 (572)	Yes	AH-1	-
L246+	2	32 (1.26)	203 (7.99)	6227 (1400)	-60 (-76)	300 (572)	Yes	AH-1	-
L263+	2	32 (1.26)	127 (5.00)	7562 (1700)	-60 (-76)	300 (572)	Yes	AH-1	-
L271+	2	32 (1.26)	406 (15.98)	7562 (1700)	-60 (-76)	300 (572)	Yes	AH-1	-
L273+	2	32 (1.26)	508 (20.00)	7562 (1700)	-60 (-76)	300 (572)	Yes	AH-1	-
L284+	2	32 (1.26)	152 (5.98)	8896 (2000)	-60 (-76)	300 (572)	Yes	AH-1	-
L288+	2	32 (1.26)	254 (10.00)	8896 (2000)	-60 (-76)	300 (572)	Yes	AH-1	-
L290+	2	32 (1.26)	356 (14.02)	8896 (2000)	-60 (-76)	300 (572)	Yes	AH-1	✓ Accept
L292+	2	32 (1.26)	457 (17.99)	8896 (2000)	-60 (-76)	300 (572)	Yes	AH-1	-

[Learn More](#)


### Band-IT Coated Metallic Cable Ties Investigated to CAN/CSA-C22.2 No. 62275

Cat. No.	Type Dsg.	Bundle Diam., mm(in.)		Loop Tensile Str., N(lbf)	Operating Temp., °C(°F)		Resistant to UV Light	Plenum Rating	Also Classified to [^] IEC 62275 and EN 62275
		Min	Max		Min	Max			
<b>AA111</b>	21	25.4 (1.00)	38.1 (1.50)	334 (75)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>AA112</b>	21	25.4 (1.00)	63.5 (2.50)	334 (75)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>AA113</b>	21	25.4 (1.00)	86.4 (3.40)	334 (75)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>AA114</b>	21	25.4 (1.00)	137.2 (5.40)	334 (75)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>AA115</b>	21	25.4 (1.00)	185.4 (7.30)	334 (75)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>AA311</b>	21	25.4 (1.00)	38.1 (1.50)	445 (100)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>AA312</b>	21	25.4 (1.00)	63.5 (2.50)	445 (100)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>AA313</b>	21	25.4 (1.00)	86.4 (3.40)	445 (100)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>AA314</b>	21	25.4 (1.00)	137.2 (5.40)	445 (100)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>AA315</b>	21	25.4 (1.00)	185.4 (7.30)	445 (100)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>AA316</b>	21	25.4 (1.00)	231.1 (9.10)	445 (100)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>AA317</b>	21	25.4 (1.00)	279.4 (11.00)	445 (100)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>AE111</b>	21	31.75 (1.25)	38.1 (1.50)	334 (75)	-40 (-40)	150 (302)	Yes	-	-
<b>AE112</b>	21	31.75 (1.25)	63.5 (2.50)	334 (75)	-40 (-40)	150 (302)	Yes	-	-
<b>AE113</b>	21	31.75 (1.25)	86.4 (3.40)	334 (75)	-40 (-40)	150 (302)	Yes	-	-
<b>AE114</b>	21	31.75 (1.25)	137.2 (5.40)	334 (75)	-40 (-40)	150 (302)	Yes	-	-
<b>AE115</b>	21	31.75 (1.25)	185.4 (7.30)	334 (75)	-40 (-40)	150 (302)	Yes	-	-
<b>AE311</b>	21	31.75 (1.25)	38.1 (1.50)	445 (100)	-40 (-40)	150 (302)	Yes	-	
<b>AE312</b>	21	31.75 (1.25)	63.5 (2.50)	445 (100)	-40 (-40)	150 (302)	Yes	-	-

Learn More

<b>AE313</b>	21	31.75 (1.25)	86.4 (3.40)	445 (100)	-40 (-40)	150 (302)	Yes	-	-
<b>AE314</b>	21	31.75 (1.25)	137.2 (5.40)	445 (100)	-40 (-40)	150 (302)	Yes	-	-
<b>AE315</b>	21	31.75 (1.25)	185.4 (7.30)	445 (100)	-40 (-40)	150 (302)	Yes	-	-
<b>AE316</b>	21	31.75 (1.25)	231.1 (9.10)	445 (100)	-40 (-40)	150 (302)	Yes	-	-
<b>AE317</b>	21	31.75 (1.25)	279.4 (11.00)	445 (100)	-40 (-40)	150 (302)	Yes	-	-
<b>AM111</b>	21	25.4 (1.00)	38.1 (1.50)	334 (75)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>AM112</b>	21	25.4 (1.00)	63.5 (2.50)	334 (75)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>AM113</b>	21	25.4 (1.00)	86.4 (3.40)	334 (75)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>AM114</b>	21	25.4 (1.00)	137.2 (5.40)	334 (75)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>AM115</b>	21	25.4 (1.00)	185.4 (7.30)	334 (75)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>AM311</b>	21	25.4 (1.00)	38.1 (1.50)	445 (100)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>AM312</b>	21	25.4 (1.00)	63.5 (2.50)	445 (100)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>AM313</b>	21	25.4 (1.00)	86.4 (3.40)	445 (100)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>AM314</b>	21	25.4 (1.00)	137.2 (5.40)	445 (100)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>AM315</b>	21	25.4 (1.00)	185.4 (7.30)	445 (100)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>AM316</b>	21	25.4 (1.00)	231.1 (9.10)	445 (100)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>AM317</b>	21	25.4 (1.00)	279.4 (11.00)	445 (100)	-40 (-40)	150 (302)	Yes	AH-2	-

**Coated Metallic Cable Ties Investigated to CAN/CSA-C22.2 No. 62275**

Cat. No.	Type Dsg.	Bundle Diam., mm(in.)		Loop Tensile Str., N(lbf)	Operating Temp., °C(°F)		Resistant to UV Light	Plenum Rating	Also Classified to [^] IEC 62275 and EN 62275
		Min	Max		Min	Max			
<b>KT4B046-0100</b>	2	12.7 (0.50)	25 (0.98)	710 (160)	-40 (-40)	150 (302)	Yes	-	
<b>KT4B046-0150</b>	2	12.7 (0.50)	37 (1.46)	710 (160)	-40 (-40)	150 (302)	Yes	-	-

Learn More

<b>KT4B046-0200</b>	2	12.7 (0.50)	50 (1.97)	710 (160)	-40 (-40)	150 (302)	Yes	-	-
<b>KT4B046-0250</b>	2	12.7 (0.50)	63 (2.48)	710 (160)	-40 (-40)	150 (302)	Yes	-	-
<b>KT4B046-0300</b>	2	12.7 (0.50)	76 (2.99)	710 (160)	-40 (-40)	150 (302)	Yes	-	-
<b>KT4B046-0350</b>	2	12.7 (0.50)	89 (3.50)	710 (160)	-40 (-40)	150 (302)	Yes	-	-
<b>KT4B046-0400</b>	2	12.7 (0.50)	102 (4.02)	710 (160)	-40 (-40)	150 (302)	Yes	-	-
<b>KT4B046-0450</b>	2	12.7 (0.50)	115 (4.53)	710 (160)	-40 (-40)	150 (302)	Yes	-	-
<b>KT4B046-0500</b>	2	12.7 (0.50)	128 (5.04)	710 (160)	-40 (-40)	150 (302)	Yes	-	-
<b>KT4B078-0150</b>	2	12.7 (0.50)	37 (1.46)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-
<b>KT4B078-0200</b>	2	12.7 (0.50)	50 (1.97)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-
<b>KT4B078-0250</b>	2	12.7 (0.50)	63 (2.48)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-
<b>KT4B078-0300</b>	2	12.7 (0.50)	76 (2.99)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-
<b>KT4B078-0350</b>	2	12.7 (0.50)	89 (3.50)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-
<b>KT4B078-0400</b>	2	12.7 (0.50)	102 (4.02)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-
<b>KT4B078-0450</b>	2	12.7 (0.50)	115 (4.53)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-
<b>KT4B078-0500</b>	2	12.7 (0.50)	128 (5.04)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-
<b>KT4B078-0550</b>	2	12.7 (0.50)	141 (5.55)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-
<b>KT4B078-0600</b>	2	12.7 (0.50)	154 (6.06)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-
<b>KT4B120-0150</b>	2	25.4 (1.00)	50 (1.97)	2000 (450)	-40 (-40)	150 (302)	Yes	-	-
<b>KT4B120-0200</b>	2	25.4 (1.00)	63 (2.48)	2000 (450)	-40 (-40)	150 (302)	Yes	-	-
<b>KT4B120-0250</b>	2	25.4 (1.00)	76 (2.99)	2000 (450)	-40 (-40)	150 (302)	Yes	-	-
<b>KT4B120-0300</b>	2	25.4 (1.00)	89 (3.50)	2000 (450)	-40 (-40)	150 (302)	Yes	-	-
<b>KT4B120-0350</b>	2	25.4 (1.00)	102 (4.02)	2000 (450)	-40 (-40)	150 (302)	Yes	-	-

[Learn More](#)

<b>KT4B120-0400</b>	2	25.4 (1.00)	115 (4.53)	2000 (450)	-40 (-40)	150 (302)	Yes	-	-
<b>KT4B120-0450</b>	2	25.4 (1.00)	128 (5.04)	2000 (450)	-40 (-40)	150 (302)	Yes	-	-
<b>KT4B120-0500</b>	2	25.4 (1.00)	141 (5.55)	2000 (450)	-40 (-40)	150 (302)	Yes	-	-
<b>KT4B120-0550</b>	2	25.4 (1.00)	154 (6.06)	2000 (450)	-40 (-40)	150 (302)	Yes	-	-
<b>KT4B120-0600</b>	2	25.4 (1.00)	167 (6.57)	2000 (450)	-40 (-40)	150 (302)	Yes	-	-
<b>KT4B150-0150</b>	2	25.4 (1.00)	76 (2.99)	3000 (674)	-40 (-40)	150 (302)	Yes	-	-
<b>KT4B150-0200</b>	2	25.4 (1.00)	89 (3.50)	3000 (674)	-40 (-40)	150 (302)	Yes	-	-
<b>KT4B150-0250</b>	2	25.4 (1.00)	102 (4.02)	3000 (674)	-40 (-40)	150 (302)	Yes	-	-
<b>KT4B150-0300</b>	2	25.4 (1.00)	115 (4.53)	3000 (674)	-40 (-40)	150 (302)	Yes	-	-
<b>KT4B150-0350</b>	2	25.4 (1.00)	128 (5.04)	3000 (674)	-40 (-40)	150 (302)	Yes	-	-
<b>KT4B150-0400</b>	2	25.4 (1.00)	141 (5.55)	3000 (674)	-40 (-40)	150 (302)	Yes	-	-
<b>KT4B150-0450</b>	2	25.4 (1.00)	154 (6.06)	3000 (674)	-40 (-40)	150 (302)	Yes	-	-
<b>KT4B150-0500</b>	2	25.4 (1.00)	167 (6.57)	3000 (674)	-40 (-40)	150 (302)	Yes	-	-
<b>KT4B150-0550</b>	2	25.4 (1.00)	180 (7.09)	3000 (674)	-40 (-40)	150 (302)	Yes	-	-
<b>KT4B150-0600</b>	2	25.4 (1.00)	193 (7.60)	3000 (674)	-40 (-40)	150 (302)	Yes	-	-

**Epoxy Coated-Metallic Cable Ties Investigated to CAN/CSA-C22.2 No. 62275**


Cat. No.	Type Dsg.	Bundle Diam., mm(in.)		Loop Tensile Str., N(lbf)	Operating Temp., °C(°F)		Resistant to UV Light	Plenum Rating	Also Classified to [^] IEC 62275 and EN 62275
		Min	Max		Min	Max			
<b>KE02AAUK</b>	21	20 (0.79)	30-305 (1.18)	667 (150)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>KE04BBUK</b>	21	20 (0.79)	51-305 (2.01)	778 (175)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>XE02AAUK</b>	21	20 (0.79)	30-305 (1.18)	667 (150)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>XE04AAUK</b>	21	20 (0.79)	30-305 (1.18)	778 (175)	-40 (-40)	150 (302)	Yes	AH-2	-

[Learn More](#)

## Free-End Clip Un-Coated Metallic Cable Ties Investigated to CAN/CSA-C22.2 No. 62275

Cat. No.	Type Dsg.	Bundle Diam., mm(in.)		Loop Tensile Str., N(lbf)	Operating Temp., °C(°F)		Resistant to UV Light	Plenum Rating	Also Classified to [^] IEC 62275 and EN 62275
		Min	Max		Min	Max			
		<b>L203</b>	2		19 (0.75)	51 (2.01)			
<b>L204</b>	2	19 (0.75)	89 (3.50)	2001 (450)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>L207</b>	2	19 (0.75)	127 (5.00)	2001 (450)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>L208</b>	2	19 (0.75)	178 (7.01)	2001 (450)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>L210</b>	2	19 (0.75)	229 (9.02)	2001 (450)	-60 (-76)	300 (572)	Yes	AH-1	-

## Metallic Cable Ties Investigated to CAN/CSA-C22.2 No. 62275

Cat. No.	Type Dsg.	Bundle Diam., mm(in.)		Loop Tensile Str., N(lbf)	Operating Temp., °C(°F)		Resistant to UV Light	Plenum Rating	Also Classified to [^] IEC 62275 and EN 62275
		Min	Max		Min	Max			
		<b>KT4U046-0100</b>	2		12.7 (0.50)	25 (0.98)			
<b>KT4U046-0150</b>	2	12.7 (0.50)	37 (1.46)	1000 (225)	-60 (-76)	300 (572)	Yes	-	-
<b>KT4U046-0200</b>	2	12.7 (0.50)	50 (1.97)	1000 (225)	-60 (-76)	300 (572)	Yes	-	-
<b>KT4U046-0250</b>	2	12.7 (0.50)	63 (2.48)	1000 (225)	-60 (-76)	300 (572)	Yes	-	-
<b>KT4U046-0300</b>	2	12.7 (0.50)	76 (2.99)	1000 (225)	-60 (-76)	300 (572)	Yes	-	-
<b>KT4U046-0350</b>	2	12.7 (0.50)	89 (3.50)	1000 (225)	-60 (-76)	300 (572)	Yes	-	-
<b>KT4U046-0400</b>	2	12.7 (0.50)	102 (4.02)	1000 (225)	-60 (-76)	300 (572)	Yes	-	-
<b>KT4U046-0450</b>	2	12.7 (0.50)	115 (4.53)	1000 (225)	-60 (-76)	300 (572)	Yes	-	-
<b>KT4U046-0500</b>	2	12.7 (0.50)	128 (5.04)	1000 (225)	-60 (-76)	300 (572)	Yes	-	
<b>KT4U078-0150</b>	2	12.7 (0.50)	50 (1.97)	2220 (499)	-60 (-76)	300 (572)	Yes	-	-


[. Learn More](#)

<b>KT4U078-0200</b>	2	12.7 (0.50)	63 (2.48)	2220 (499)	-60 (-76)	300 (572)	Yes	-	-
<b>KT4U078-0250</b>	2	12.7 (0.50)	76 (2.99)	2220 (499)	-60 (-76)	300 (572)	Yes	-	-
<b>KT4U078-0300</b>	2	12.7 (0.50)	89 (3.50)	2220 (499)	-60 (-76)	300 (572)	Yes	-	-
<b>KT4U078-0350</b>	2	12.7 (0.50)	102 (4.02)	2220 (499)	-60 (-76)	300 (572)	Yes	-	-
<b>KT4U078-0400</b>	2	12.7 (0.50)	115 (4.53)	2220 (499)	-60 (-76)	300 (572)	Yes	-	-
<b>KT4U078-0450</b>	2	12.7 (0.50)	128 (5.04)	2220 (499)	-60 (-76)	300 (572)	Yes	-	-
<b>KT4U078-0500</b>	2	12.7 (0.50)	141 (5.55)	2220 (499)	-60 (-76)	300 (572)	Yes	-	-
<b>KT4U078-0550</b>	2	12.7 (0.50)	154 (6.06)	2220 (499)	-60 (-76)	300 (572)	Yes	-	-
<b>KT4U078-0600</b>	2	12.7 (0.50)	167 (6.57)	2220 (499)	-60 (-76)	300 (572)	Yes	-	-
<b>KT4U120-0150</b>	2	25.4 (1.00)	50 (1.97)	3115 (700)	-60 (-76)	300 (572)	Yes	-	-
<b>KT4U120-0200</b>	2	25.4 (1.00)	63 (2.48)	3115 (700)	-60 (-76)	300 (572)	Yes	-	-
<b>KT4U120-0250</b>	2	25.4 (1.00)	76 (2.99)	3115 (700)	-60 (-76)	300 (572)	Yes	-	-
<b>KT4U120-0300</b>	2	25.4 (1.00)	89 (3.50)	3115 (700)	-60 (-76)	300 (572)	Yes	-	-
<b>KT4U120-0350</b>	2	25.4 (1.00)	102 (4.02)	3115 (700)	-60 (-76)	300 (572)	Yes	-	-
<b>KT4U120-0400</b>	2	25.4 (1.00)	115 (4.53)	3115 (700)	-60 (-76)	300 (572)	Yes	-	-
<b>KT4U120-0450</b>	2	25.4 (1.00)	128 (5.04)	3115 (700)	-60 (-76)	300 (572)	Yes	-	-
<b>KT4U120-0500</b>	2	25.4 (1.00)	141 (5.55)	3115 (700)	-60 (-76)	300 (572)	Yes	-	-
<b>KT4U120-0550</b>	2	25.4 (1.00)	154 (6.06)	3115 (700)	-60 (-76)	300 (572)	Yes	-	-
<b>KT4U120-0600</b>	2	25.4 (1.00)	167 (6.57)	3115 (700)	-60 (-76)	300 (572)	Yes	-	-
<b>KT4U150-0150</b>	2	25.4 (1.00)	76 (2.99)	4100 (922)	-60 (-76)	300 (572)	Yes	-	-
<b>KT4U150-0200</b>	2	25.4 (1.00)	89 (3.50)	4100 (922)	-60 (-76)	300 (572)	Yes	-	-
<b>KT4U150-0250</b>	2	25.4 (1.00)	102 (4.02)	4100 (922)	-60 (-76)	300 (572)	Yes	-	-

[Learn More](#)

<b>KT4U150-0300</b>	2	25.4 (1.00)	115 (4.53)	4100 (922)	-60 (-76)	300 (572)	Yes	-	-
<b>KT4U150-0350</b>	2	25.4 (1.00)	128 (5.04)	4100 (922)	-60 (-76)	300 (572)	Yes	-	-
<b>KT4U150-0400</b>	2	25.4 (1.00)	141 (5.55)	4100 (922)	-60 (-76)	300 (572)	Yes	-	-
<b>KT4U150-0450</b>	2	25.4 (1.00)	154 (6.06)	4100 (922)	-60 (-76)	300 (572)	Yes	-	-
<b>KT4U150-0500</b>	2	25.4 (1.00)	167 (6.57)	4100 (922)	-60 (-76)	300 (572)	Yes	-	-
<b>KT4U150-0550</b>	2	25.4 (1.00)	180 (7.09)	4100 (922)	-60 (-76)	300 (572)	Yes	-	-
<b>KT4U150-0600</b>	2	25.4 (1.00)	193 (7.60)	4100 (922)	-60 (-76)	300 (572)	Yes	-	-

**Multi-Lok Coated Metallic Cable Ties Investigated to CAN/CSA-C22.2 No. 62275**

Cat. No.	Type Dsg.	Bundle Diam., mm(in.)		Loop Tensile Str., N(lbf)	Operating Temp., °C(°F)		Resistant to UV Light	Plenum Rating	Also Classified to IEC 62275 and EN 62275 [^]
		Min	Max		Min	Max			
<b>AE611</b>	21	19 (0.75)	33.0 (1.30)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-
<b>AE612</b>	21	19 (0.75)	55.9 (2.20)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-
<b>AE613</b>	21	19 (0.75)	81.3 (3.20)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-
<b>AE614</b>	21	19 (0.75)	130.0 (5.12)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-
<b>AE615</b>	21	19 (0.75)	180.3 (7.10)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-
<b>AE711</b>	21	19 (0.75)	33.0 (1.30)	1846 (415)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>AE712</b>	21	19 (0.75)	55.9 (2.20)	1846 (415)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>AE713</b>	21	19 (0.75)	81.3 (3.20)	1846 (415)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>AE714</b>	21	19 (0.75)	130.0 (5.12)	1846 (415)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>AE715</b>	21	19 (0.75)	180.3 (7.10)	1846 (415)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>AM611</b>	21	19 (0.75)	33.0 (1.30)	1112 (250)	-40 (-40)	150 (302)	Yes	-	
<b>AM612</b>	21	19 (0.75)	55.9 (2.20)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-


[Learn More](#)



<b>AM613</b>	21	19 (0.75)	81.3 (3.20)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-
<b>AM614</b>	21	19 (0.75)	130.0 (5.12)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-
<b>AM615</b>	21	19 (0.75)	180.3 (7.10)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-
<b>AM711</b>	21	19 (0.75)	33.0 (1.30)	1846 (415)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>AM712</b>	21	19 (0.75)	55.9 (2.20)	1846 (415)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>AM713</b>	21	19 (0.75)	81.3 (3.20)	1846 (415)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>AM714</b>	21	19 (0.75)	130.0 (5.12)	1846 (415)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>AM715</b>	21	19 (0.75)	180.3 (7.10)	1846 (415)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>TB611</b>	21	19 (0.75)	33.0 (1.30)	1112 (250)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>TB612</b>	21	19 (0.75)	55.9 (2.20)	1112 (250)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>TB613</b>	21	19 (0.75)	81.3 (3.20)	1112 (250)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>TB614</b>	21	19 (0.75)	130.0 (5.12)	1112 (250)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>TB615</b>	21	19 (0.75)	180.3 (7.10)	1112 (250)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>TB711</b>	21	19 (0.75)	33.0 (1.30)	1112 (250)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>TB712</b>	21	19 (0.75)	55.9 (2.20)	1112 (250)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>TB713</b>	21	19 (0.75)	81.3 (3.20)	1112 (250)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>TB714</b>	21	19 (0.75)	130.0 (5.12)	1112 (250)	-40 (-40)	150 (302)	Yes	AH-2	-
<b>TB715</b>	21	19 (0.75)	180.3 (7.10)	1112 (250)	-40 (-40)	150 (302)	Yes	AH-2	-

**Multi-Lok Un-Coated Metallic Cable Ties Investigated to CAN/CSA-C22.2 No. 62275**

Cat. No.	Type Dsg.	Bundle Diam.		Loop Tensile Str., N(lbf)	Operating Temp., °C(°F)		Resistant to UV Light	Plenum Rating	IEC 60332-1-2	Also Classified to CAN/CSA-C22.2 No. 62275
		Min	Max		Min	Max				
. Learn More										

<b>AE601</b>	2	19 (0.75)	33 (1.30)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>AE602</b>	2	19 (0.75)	56 (2.20)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>AE603</b>	2	19 (0.75)	81 (3.19)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>AE604</b>	2	19 (0.75)	130 (5.12)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>AE605</b>	2	19 (0.75)	180 (7.09)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>AE701</b>	2	19 (0.75)	33 (1.30)	1846 (415)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>AE702</b>	2	19 (0.75)	56 (2.20)	1846 (415)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>AE703</b>	2	19 (0.75)	81 (3.19)	1846 (415)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>AE704</b>	2	19 (0.75)	130 (5.12)	1846 (415)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>AE705</b>	2	19 (0.75)	180 (7.09)	1846 (415)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>AM601</b>	2	19 (0.75)	33 (1.30)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>AM602</b>	2	19 (0.75)	56 (2.20)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>AM603</b>	2	19 (0.75)	81 (3.19)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>AM604</b>	2	19 (0.75)	130 (5.12)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>AM605</b>	2	19 (0.75)	180 (7.09)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>AM701</b>	2	19 (0.75)	33 (1.30)	1846 (415)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>AM702</b>	2	19 (0.75)	56 (2.20)	1846 (415)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>AM703</b>	2	19 (0.75)	81 (3.19)	1846 (415)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>AM704</b>	2	19 (0.75)	130 (5.12)	1846 (415)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>AM705</b>	2	19 (0.75)	180 (7.09)	1846 (415)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>TB601</b>	2	19 (0.75)	33 (1.30)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	
<b>TB602</b>	2	19 (0.75)	56 (2.20)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-

[Learn More](#)

<b>TB603</b>	2	19 (0.75)	81 (3.19)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>TB604</b>	2	19 (0.75)	130 (5.12)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>TB605</b>	2	19 (0.75)	180 (7.09)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>TB701</b>	2	19 (0.75)	33 (1.30)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>TB702</b>	2	19 (0.75)	56 (2.20)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>TB703</b>	2	19 (0.75)	81 (3.19)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>TB704</b>	2	19 (0.75)	130 (5.12)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>TB705</b>	2	19 (0.75)	180 (7.09)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-

### Nylon Coated-Metallic Cable Ties Investigated to CAN/CSA-C22.2 No. 62275

Cat. No.	Type Dsg.	Bundle Diam., mm(in.)		Loop Tensile Str., N(lbf)	Operating Temp., °C(°F)		Resistant to UV Light	Plenum Rating	Also Classified to [^] IEC 62275 and EN 62275
		Min	Max		Min	Max			
<b>KE06AA</b>	21	20 (0.79)	30-254 (1.18)	444 (100)	-40 (-40)	140 (284)	Yes	AH-2	-
<b>KE08AA</b>	21	20 (0.79)	30-254 (1.18)	533 (120)	-40 (-40)	140 (284)	Yes	AH-2	-

### S.I.D. Tie-Lok Un-Coated Metallic Cable Ties Investigated to CAN/CSA-C22.2 No. 62275

Cat. No.	Type Dsg.	Bundle Diam., mm(in.)		Loop Tensile Str., N(lbf)	Operating Temp., °C(°F)		Resistant to UV Light	Plenum Rating	Also Classified to [^] IEC 62275 and EN 62275
		Min	Max		Min	Max			
<b>AM211</b>	2	12.7 (0.50)	50.8 (2.00)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>AM212</b>	2	12.7 (0.50)	102 (4.02)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>AM213</b>	2	12.7 (0.50)	152 (5.98)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>AM214</b>	2	12.7 (0.50)	203 (7.99)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>AM215</b>	2	12.7 (0.50)	254 (10.00)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-

[. Learn More](#)

<b>AS211</b>	2	12.7 (0.50)	50.8 (2.00)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>AS212</b>	2	12.7 (0.50)	102 (4.02)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>AS213</b>	2	12.7 (0.50)	152 (5.98)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>AS214</b>	2	12.7 (0.50)	203 (7.99)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>AS215</b>	2	12.7 (0.50)	254 (10.00)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>AS221</b>	2	12.7 (0.50)	25.4 (1.00)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>AS222</b>	2	12.7 (0.50)	50.8 (2.00)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>AS223</b>	2	12.7 (0.50)	102 (4.02)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>AS224</b>	2	12.7 (0.50)	152 (5.98)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>AS225</b>	2	12.7 (0.50)	203 (7.99)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>AS411</b>	2	12.7 (0.50)	50.8 (2.00)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>AS412</b>	2	12.7 (0.50)	102 (4.02)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>AS413</b>	2	12.7 (0.50)	152 (5.98)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>AS414</b>	2	12.7 (0.50)	203 (7.99)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>AS415</b>	2	12.7 (0.50)	254 (10.00)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>AS421</b>	2	12.7 (0.50)	25.4 (1.00)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>AS422</b>	2	12.7 (0.50)	50.8 (2.00)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>AS423</b>	2	12.7 (0.50)	102 (4.02)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>AS424</b>	2	12.7 (0.50)	152 (5.98)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>AS425</b>	2	12.7 (0.50)	203 (7.99)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1	-

Un-Coated Metallic Cable Ties Investigated to CAN/CSA-C22.5

. Learn More

Cat. No.	Type Dsg.	Bundle Diam., mm(in.)		Loop Tensile Str., N(lbf)	Operating Temp., °C(°F)		Resistant to UV Light	Plenum Rating	Also Classified to [^] IEC 62275 and EN 62275
		Min	Max		Min	Max			
		<b>KE01AAUK</b>	2		20 (0.79)	30-305 (1.18)			
<b>KE03AAUK</b>	2	20 (0.79)	30-305 (1.18)	1334 (300)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>KE11AAUK</b>	2	20 (0.79)	30-305 (1.18)	890 (200)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>KE13AAUK</b>	2	20 (0.79)	30-338 (1.18)	1334 (300)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>XE01AAUK</b>	2	20 (0.79)	30-305 (1.18)	890 (200)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>XE03AAUK</b>	2	20 (0.79)	30-305 (1.18)	1334 (300)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>XE11AAUK</b>	2	20 (0.79)	30-305 (1.18)	890 (200)	-60 (-76)	300 (572)	Yes	AH-1	-
<b>XE13AAUK</b>	2	20 (0.79)	30-338 (1.18)	1334 (300)	-60 (-76)	300 (572)	Yes	AH-1	-

+ - Optionally prefixed by T as related to packing requirements and a numeric suffix related to packaging quantity.

Note - All cable ties designations may include an alphanumeric suffix related to packaging requirements and quantity.

Last Updated on 2018-03-06

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"



[. Learn More](#)