

ZODZ.E157233 - POSITIONING DEVICES

Positioning Devices

See General Information for Positioning Devices

BAND-IT-IDEX INC

E157233

4799 Dahlia St
Denver, CO 80216 USA

Band-Fast Un-Coated Metallic Cable Ties Investigated to ANSI/UL 62275

Cat. No.	Type Dsg.	Bundle Diam., mm(in.)		Loop Tensile Str., N(lbf)	Operating Temp., °C(°F)		Resistant to UV Light	Plenum Rating	Also Classified to IEC 62275 and EN 62275 [^]	
		Min	Max		Min	Max				
L221+	2	25.4 (1.00)	89 (3.50)	4003 (900)	-60 (-76)	300 (572)	Yes	AH-1		-
L229+	2	25.4 (1.00)	305 (12.01)	4003 (900)	-60 (-76)	300 (572)	Yes	AH-1		-
L242+	2	32 (1.26)	102 (4.02)	6227 (1400)	-60 (-76)	300 (572)	Yes	AH-1		-
L246+	2	32 (1.26)	203 (7.99)	6227 (1400)	-60 (-76)	300 (572)	Yes	AH-1		-
L263+	2	32 (1.26)	127 (5.00)	7562 (1700)	-60 (-76)	300 (572)	Yes	AH-1		-
L271+	2	32 (1.26)	406 (15.98)	7562 (1700)	-60 (-76)	300 (572)	Yes	AH-1		-
L273+	2	32 (1.26)	508 (20.00)	7562 (1700)	-60 (-76)	300 (572)	Yes	AH-1		-
L284+	2	32 (1.26)	152 (5.98)	8896 (2000)	-60 (-76)	300 (572)	Yes	AH-1		-
L288+	2	32 (1.26)	254 (10.00)	8896 (2000)	-60 (-76)	300 (572)	Yes	AH-1		-
L290+	2	32 (1.26)	356 (14.02)	8896 (2000)	-60 (-76)	300 (572)	Yes	AH-1		-
L292+	2	32 (1.26)	457 (17.99)	8896 (2000)	-60 (-76)	300 (572)	Yes	AH-1	✓ Accept	-

Band-IT Coated Metallic Cable Ties Investigated to ANSI/UL 62275

[. Learn More](#)


Cat. No.	Type Dsg.	Bundle Diam., mm(in.)		Loop Tensile Str., N(lbf)	Operating Temp., °C(°F)		Resistant to UV Light	Plenum Rating	Also Classified to [^] IEC 62275 and EN 62275
		Min	Max		Min	Max			
		AA111	21		25.4 (1.00)	38.1 (1.50)			
AA112	21	25.4 (1.00)	63.5 (2.50)	334 (75)	-40 (-40)	150 (302)	Yes	AH-2	-
AA113	21	25.4 (1.00)	86.4 (3.40)	334 (75)	-40 (-40)	150 (302)	Yes	AH-2	-
AA114	21	25.4 (1.00)	137.2 (5.40)	334 (75)	-40 (-40)	150 (302)	Yes	AH-2	-
AA115	21	25.4 (1.00)	185.4 (7.30)	334 (75)	-40 (-40)	150 (302)	Yes	AH-2	-
AA311	21	25.4 (1.00)	38.1 (1.50)	445 (100)	-40 (-40)	150 (302)	Yes	AH-2	-
AA312	21	25.4 (1.00)	63.5 (2.50)	445 (100)	-40 (-40)	150 (302)	Yes	AH-2	-
AA313	21	25.4 (1.00)	86.4 (3.40)	445 (100)	-40 (-40)	150 (302)	Yes	AH-2	-
AA314	21	25.4 (1.00)	137.2 (5.40)	445 (100)	-40 (-40)	150 (302)	Yes	AH-2	-
AA315	21	25.4 (1.00)	185.4 (7.30)	445 (100)	-40 (-40)	150 (302)	Yes	AH-2	-
AA316	21	25.4 (1.00)	231.1 (9.10)	445 (100)	-40 (-40)	150 (302)	Yes	AH-2	-
AA317	21	25.4 (1.00)	279.4 (11.00)	445 (100)	-40 (-40)	150 (302)	Yes	AH-2	-
AE111	21	31.75 (1.25)	38.1 (1.50)	334 (75)	-40 (-40)	150 (302)	Yes	-	-
AE112	21	31.75 (1.25)	63.5 (2.50)	334 (75)	-40 (-40)	150 (302)	Yes	-	-
AE113	21	31.75 (1.25)	86.4 (3.40)	334 (75)	-40 (-40)	150 (302)	Yes	-	-
AE114	21	31.75 (1.25)	137.2 (5.40)	334 (75)	-40 (-40)	150 (302)	Yes	-	-
AE115	21	31.75 (1.25)	185.4 (7.30)	334 (75)	-40 (-40)	150 (302)	Yes	-	-
AE311	21	31.75 (1.25)	38.1 (1.50)	445 (100)	-40 (-40)	150 (302)	Yes	-	-
AE312	21	31.75 (1.25)	63.5 (2.50)	445 (100)	-40 (-40)	150 (302)	Yes	-	-
AE313	21	31.75 (1.25)	86.4 (3.40)	445 (100)	-40 (-40)	150 (302)	Yes	-	-

Learn More




AE314	21	31.75 (1.25)	137.2 (5.40)	445 (100)	-40 (-40)	150 (302)	Yes	-	-
AE315	21	31.75 (1.25)	185.4 (7.30)	445 (100)	-40 (-40)	150 (302)	Yes	-	-
AE316	21	31.75 (1.25)	231.1 (9.10)	445 (100)	-40 (-40)	150 (302)	Yes	-	-
AE317	21	31.75 (1.25)	279.4 (11.00)	445 (100)	-40 (-40)	150 (302)	Yes	-	-
AM111	21	25.4 (1.00)	38.1 (1.50)	334 (75)	-40 (-40)	150 (302)	Yes	AH-2	-
AM112	21	25.4 (1.00)	63.5 (2.50)	334 (75)	-40 (-40)	150 (302)	Yes	AH-2	-
AM113	21	25.4 (1.00)	86.4 (3.40)	334 (75)	-40 (-40)	150 (302)	Yes	AH-2	-
AM114	21	25.4 (1.00)	137.2 (5.40)	334 (75)	-40 (-40)	150 (302)	Yes	AH-2	-
AM115	21	25.4 (1.00)	185.4 (7.30)	334 (75)	-40 (-40)	150 (302)	Yes	AH-2	-
AM311	21	25.4 (1.00)	38.1 (1.50)	445 (100)	-40 (-40)	150 (302)	Yes	AH-2	-
AM312	21	25.4 (1.00)	63.5 (2.50)	445 (100)	-40 (-40)	150 (302)	Yes	AH-2	-
AM313	21	25.4 (1.00)	86.4 (3.40)	445 (100)	-40 (-40)	150 (302)	Yes	AH-2	-
AM314	21	25.4 (1.00)	137.2 (5.40)	445 (100)	-40 (-40)	150 (302)	Yes	AH-2	-
AM315	21	25.4 (1.00)	185.4 (7.30)	445 (100)	-40 (-40)	150 (302)	Yes	AH-2	-
AM316	21	25.4 (1.00)	231.1 (9.10)	445 (100)	-40 (-40)	150 (302)	Yes	AH-2	-
AM317	21	25.4 (1.00)	279.4 (11.00)	445 (100)	-40 (-40)	150 (302)	Yes	AH-2	-

Coated Metallic Cable Ties Investigated to ANSI/UL 62275

Cat. No.	Type Dsg.	Bundle Diam., mm(in.)		Loop Tensile Str., N(lbf)	Operating Temp., °C(°F)		Resistant to UV Light	Plenum Rating	Also Classified to [^] IEC 62275 and EN 62275
		Min	Max		Min	Max			
KT4B046-0100	2	12.7 (0.50)	25 (0.98)	710 (160)	-40 (-40)	150 (302)	Yes	-	-
KT4B046-0150	2	12.7 (0.50)	37 (1.46)	710 (160)	-40 (-40)	150 (302)	Yes	-	
KT4B046-0200	2	12.7 (0.50)	50 (1.97)	710 (160)	-40 (-40)	150 (302)	Yes	-	-

[Learn More](#)

KT4B046-0250	2	12.7 (0.50)	63 (2.48)	710 (160)	-40 (-40)	150 (302)	Yes	-	-
KT4B046-0300	2	12.7 (0.50)	76 (2.99)	710 (160)	-40 (-40)	150 (302)	Yes	-	-
KT4B046-0350	2	12.7 (0.50)	89 (3.50)	710 (160)	-40 (-40)	150 (302)	Yes	-	-
KT4B046-0400	2	12.7 (0.50)	102 (4.02)	710 (160)	-40 (-40)	150 (302)	Yes	-	-
KT4B046-0450	2	12.7 (0.50)	115 (4.53)	710 (160)	-40 (-40)	150 (302)	Yes	-	-
KT4B046-0500	2	12.7 (0.50)	128 (5.04)	710 (160)	-40 (-40)	150 (302)	Yes	-	-
KT4B078-0150	2	12.7 (0.50)	37 (1.46)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-
KT4B078-0200	2	12.7 (0.50)	50 (1.97)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-
KT4B078-0250	2	12.7 (0.50)	63 (2.48)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-
KT4B078-0300	2	12.7 (0.50)	76 (2.99)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-
KT4B078-0350	2	12.7 (0.50)	89 (3.50)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-
KT4B078-0400	2	12.7 (0.50)	102 (4.02)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-
KT4B078-0450	2	12.7 (0.50)	115 (4.53)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-
KT4B078-0500	2	12.7 (0.50)	128 (5.04)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-
KT4B078-0550	2	12.7 (0.50)	141 (5.55)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-
KT4B078-0600	2	12.7 (0.50)	154 (6.06)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-
KT4B120-0150	2	25.4 (1.00)	50 (1.97)	2000 (450)	-40 (-40)	150 (302)	Yes	-	-
KT4B120-0200	2	25.4 (1.00)	63 (2.48)	2000 (450)	-40 (-40)	150 (302)	Yes	-	-
KT4B120-0250	2	25.4 (1.00)	76 (2.99)	2000 (450)	-40 (-40)	150 (302)	Yes	-	-
KT4B120-0300	2	25.4 (1.00)	89 (3.50)	2000 (450)	-40 (-40)	150 (302)	Yes	-	-
KT4B120-0350	2	25.4 (1.00)	102 (4.02)	2000 (450)	-40 (-40)	150 (302)	Yes	-	
KT4B120-0400	2	25.4 (1.00)	115 (4.53)	2000 (450)	-40 (-40)	150 (302)	Yes	-	-

[Learn More](#)

KT4B120-0450	2	25.4 (1.00)	128 (5.04)	2000 (450)	-40 (-40)	150 (302)	Yes	-	-
KT4B120-0500	2	25.4 (1.00)	141 (5.55)	2000 (450)	-40 (-40)	150 (302)	Yes	-	-
KT4B120-0550	2	25.4 (1.00)	154 (6.06)	2000 (450)	-40 (-40)	150 (302)	Yes	-	-
KT4B120-0600	2	25.4 (1.00)	167 (6.57)	2000 (450)	-40 (-40)	150 (302)	Yes	-	-
KT4B150-0150	2	25.4 (1.00)	76 (2.99)	3000 (674)	-40 (-40)	150 (302)	Yes	-	-
KT4B150-0200	2	25.4 (1.00)	89 (3.50)	3000 (674)	-40 (-40)	150 (302)	Yes	-	-
KT4B150-0250	2	25.4 (1.00)	102 (4.02)	3000 (674)	-40 (-40)	150 (302)	Yes	-	-
KT4B150-0300	2	25.4 (1.00)	115 (4.53)	3000 (674)	-40 (-40)	150 (302)	Yes	-	-
KT4B150-0350	2	25.4 (1.00)	128 (5.04)	3000 (674)	-40 (-40)	150 (302)	Yes	-	-
KT4B150-0400	2	25.4 (1.00)	141 (5.55)	3000 (674)	-40 (-40)	150 (302)	Yes	-	-
KT4B150-0450	2	25.4 (1.00)	154 (6.06)	3000 (674)	-40 (-40)	150 (302)	Yes	-	-
KT4B150-0500	2	25.4 (1.00)	167 (6.57)	3000 (674)	-40 (-40)	150 (302)	Yes	-	-
KT4B150-0550	2	25.4 (1.00)	180 (7.09)	3000 (674)	-40 (-40)	150 (302)	Yes	-	-
KT4B150-0600	2	25.4 (1.00)	193 (7.60)	3000 (674)	-40 (-40)	150 (302)	Yes	-	-

Epoxy Coated-Metallic Cable Ties Investigated to ANSI/UL 62275

Cat. No.	Type Dsg.	Bundle Diam., mm(in.)		Loop Tensile Str., N(lbf)	Operating Temp., °C(°F)		Resistant to UV Light	Plenum Rating	Also Classified to [^] IEC 62275 and EN 62275
		Min	Max		Min	Max			
KE02AAUK	21	20 (0.79)	30-305 (1.18)	667 (150)	-40 (-40)	150 (302)	Yes	AH-2	-
KE04BBUK	21	20 (0.79)	51-305 (2.01)	778 (175)	-40 (-40)	150 (302)	Yes	AH-2	-
XE02AAUK	21	20 (0.79)	30-305 (1.18)	667 (150)	-40 (-40)	150 (302)	Yes	AH-2	-
XE04AAUK	21	20 (0.79)	30-305 (1.18)	778 (175)	-40 (-40)	150 (302)	Yes	AH-2	-

Free-End Clip Un-Coated Metallic Cable Ties Investigated to ANSI/UL 62275


[Learn More](#)

Cat. No.	Type Dsg.	Bundle Diam.,		Loop Tensile Str., N(lbf)	Operating Temp., °C(°F)		Resistant to UV Light	Plenum Rating	Also Classified to [^] IEC 62275 and EN 62275
		Min	Max		Min	Max			
		mm(in.)	mm(in.)		°C(°F)	°C(°F)			
L203	2	19 (0.75)	51 (2.01)	2001 (450)	-60 (-76)	300 (572)	Yes	AH-1	-
L204	2	19 (0.75)	89 (3.50)	2001 (450)	-60 (-76)	300 (572)	Yes	AH-1	-
L207	2	19 (0.75)	127 (5.00)	2001 (450)	-60 (-76)	300 (572)	Yes	AH-1	-
L208	2	19 (0.75)	178 (7.01)	2001 (450)	-60 (-76)	300 (572)	Yes	AH-1	-
L210	2	19 (0.75)	229 (9.02)	2001 (450)	-60 (-76)	300 (572)	Yes	AH-1	-

Metallic Cable Ties Investigated to ANSI/UL 62275

Cat. No.	Type Dsg.	Bundle Diam.,		Loop Tensile Str., N(lbf)	Operating Temp., °C(°F)		Resistant to UV Light	Plenum Rating	Also Classified to [^] IEC 62275 and EN 62275
		Min	Max		Min	Max			
		mm(in.)	mm(in.)		°C(°F)	°C(°F)			
KT4U046-0100	2	12.7 (0.50)	25 (0.98)	1000 (225)	-60 (-76)	300 (572)	Yes	-	-
KT4U046-0150	2	12.7 (0.50)	37 (1.46)	1000 (225)	-60 (-76)	300 (572)	Yes	-	-
KT4U046-0200	2	12.7 (0.50)	50 (1.97)	1000 (225)	-60 (-76)	300 (572)	Yes	-	-
KT4U046-0250	2	12.7 (0.50)	63 (2.48)	1000 (225)	-60 (-76)	300 (572)	Yes	-	-
KT4U046-0300	2	12.7 (0.50)	76 (2.99)	1000 (225)	-60 (-76)	300 (572)	Yes	-	-
KT4U046-0350	2	12.7 (0.50)	89 (3.50)	1000 (225)	-60 (-76)	300 (572)	Yes	-	-
KT4U046-0400	2	12.7 (0.50)	102 (4.02)	1000 (225)	-60 (-76)	300 (572)	Yes	-	-
KT4U046-0450	2	12.7 (0.50)	115 (4.53)	1000 (225)	-60 (-76)	300 (572)	Yes	-	-
KT4U046-0500	2	12.7 (0.50)	128 (5.04)	1000 (225)	-60 (-76)	300 (572)	Yes	-	-
KT4U078-0150	2	12.7 (0.50)	50 (1.97)	2220 (499)	-60 (-76)	300 (572)	Yes	-	-
KT4U078-0200	2	12.7 (0.50)	63 (2.48)	2220 (499)	-60 (-76)	300 (572)	Yes	-	-


[. Learn More](#)

KT4U078-0250	2	12.7 (0.50)	76 (2.99)	2220 (499)	-60 (-76)	300 (572)	Yes	-	-
KT4U078-0300	2	12.7 (0.50)	89 (3.50)	2220 (499)	-60 (-76)	300 (572)	Yes	-	-
KT4U078-0350	2	12.7 (0.50)	102 (4.02)	2220 (499)	-60 (-76)	300 (572)	Yes	-	-
KT4U078-0400	2	12.7 (0.50)	115 (4.53)	2220 (499)	-60 (-76)	300 (572)	Yes	-	-
KT4U078-0450	2	12.7 (0.50)	128 (5.04)	2220 (499)	-60 (-76)	300 (572)	Yes	-	-
KT4U078-0500	2	12.7 (0.50)	141 (5.55)	2220 (499)	-60 (-76)	300 (572)	Yes	-	-
KT4U078-0550	2	12.7 (0.50)	154 (6.06)	2220 (499)	-60 (-76)	300 (572)	Yes	-	-
KT4U078-0600	2	12.7 (0.50)	167 (6.57)	2220 (499)	-60 (-76)	300 (572)	Yes	-	-
KT4U120-0150	2	25.4 (1.00)	50 (1.97)	3115 (700)	-60 (-76)	300 (572)	Yes	-	-
KT4U120-0200	2	25.4 (1.00)	63 (2.48)	3115 (700)	-60 (-76)	300 (572)	Yes	-	-
KT4U120-0250	2	25.4 (1.00)	76 (2.99)	3115 (700)	-60 (-76)	300 (572)	Yes	-	-
KT4U120-0300	2	25.4 (1.00)	89 (3.50)	3115 (700)	-60 (-76)	300 (572)	Yes	-	-
KT4U120-0350	2	25.4 (1.00)	102 (4.02)	3115 (700)	-60 (-76)	300 (572)	Yes	-	-
KT4U120-0400	2	25.4 (1.00)	115 (4.53)	3115 (700)	-60 (-76)	300 (572)	Yes	-	-
KT4U120-0450	2	25.4 (1.00)	128 (5.04)	3115 (700)	-60 (-76)	300 (572)	Yes	-	-
KT4U120-0500	2	25.4 (1.00)	141 (5.55)	3115 (700)	-60 (-76)	300 (572)	Yes	-	-
KT4U120-0550	2	25.4 (1.00)	154 (6.06)	3115 (700)	-60 (-76)	300 (572)	Yes	-	-
KT4U120-0600	2	25.4 (1.00)	167 (6.57)	3115 (700)	-60 (-76)	300 (572)	Yes	-	-
KT4U150-0150	2	25.4 (1.00)	76 (2.99)	4100 (922)	-60 (-76)	300 (572)	Yes	-	-
KT4U150-0200	2	25.4 (1.00)	89 (3.50)	4100 (922)	-60 (-76)	300 (572)	Yes	-	-
KT4U150-0250	2	25.4 (1.00)	102 (4.02)	4100 (922)	-60 (-76)	300 (572)	Yes	-	
KT4U150-0300	2	25.4 (1.00)	115 (4.53)	4100 (922)	-60 (-76)	300 (572)	Yes	-	-

[Learn More](#)

KT4U150-0350	2	25.4 (1.00)	128 (5.04)	4100 (922)	-60 (-76)	300 (572)	Yes	-	-
KT4U150-0400	2	25.4 (1.00)	141 (5.55)	4100 (922)	-60 (-76)	300 (572)	Yes	-	-
KT4U150-0450	2	25.4 (1.00)	154 (6.06)	4100 (922)	-60 (-76)	300 (572)	Yes	-	-
KT4U150-0500	2	25.4 (1.00)	167 (6.57)	4100 (922)	-60 (-76)	300 (572)	Yes	-	-
KT4U150-0550	2	25.4 (1.00)	180 (7.09)	4100 (922)	-60 (-76)	300 (572)	Yes	-	-
KT4U150-0600	2	25.4 (1.00)	193 (7.60)	4100 (922)	-60 (-76)	300 (572)	Yes	-	-


Multi-Lok Coated Metallic Cable Ties Investigated to ANSI/UL 62275

Cat. No.	Type Dsg.	Bundle Diam., mm(in.)		Loop Tensile Str., N(lbf)	Operating Temp., °C(°F)		Resistant to UV Light	Plenum Rating	Also Classified to [^]	
		Min	Max		Min	Max			IEC 62275 and EN 62275	
AE611	21	19 (0.75)	33.0 (1.30)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-	-
AE612	21	19 (0.75)	55.9 (2.20)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-	-
AE613	21	19 (0.75)	81.3 (3.20)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-	-
AE614	21	19 (0.75)	130.0 (5.12)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-	-
AE615	21	19 (0.75)	180.3 (7.10)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-	-
AE711	21	19 (0.75)	33.0 (1.30)	1846 (415)	-40 (-40)	150 (302)	Yes	AH-2	-	-
AE712	21	19 (0.75)	55.9 (2.20)	1846 (415)	-40 (-40)	150 (302)	Yes	AH-2	-	-
AE713	21	19 (0.75)	81.3 (3.20)	1846 (415)	-40 (-40)	150 (302)	Yes	AH-2	-	-
AE714	21	19 (0.75)	130.0 (5.12)	1846 (415)	-40 (-40)	150 (302)	Yes	AH-2	-	-
AE715	21	19 (0.75)	180.3 (7.10)	1846 (415)	-40 (-40)	150 (302)	Yes	AH-2	-	-
AM611	21	19 (0.75)	33.0 (1.30)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-	-
AM612	21	19 (0.75)	55.9 (2.20)	1112 (250)	-40 (-40)	150 (302)	Yes	-		-
AM613	21	19 (0.75)	81.3 (3.20)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-	-


[Learn More](#)

AM614	21	19 (0.75)	130.0 (5.12)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-
AM615	21	19 (0.75)	180.3 (7.10)	1112 (250)	-40 (-40)	150 (302)	Yes	-	-
AM711	21	19 (0.75)	33.0 (1.30)	1846 (415)	-40 (-40)	150 (302)	Yes	AH-2	-
AM712	21	19 (0.75)	55.9 (2.20)	1846 (415)	-40 (-40)	150 (302)	Yes	AH-2	-
AM713	21	19 (0.75)	81.3 (3.20)	1846 (415)	-40 (-40)	150 (302)	Yes	AH-2	-
AM714	21	19 (0.75)	130.0 (5.12)	1846 (415)	-40 (-40)	150 (302)	Yes	AH-2	-
AM715	21	19 (0.75)	180.3 (7.10)	1846 (415)	-40 (-40)	150 (302)	Yes	AH-2	-
TB611	21	19 (0.75)	33.0 (1.30)	1112 (250)	-40 (-40)	150 (302)	Yes	AH-2	-
TB612	21	19 (0.75)	55.9 (2.20)	1112 (250)	-40 (-40)	150 (302)	Yes	AH-2	-
TB613	21	19 (0.75)	81.3 (3.20)	1112 (250)	-40 (-40)	150 (302)	Yes	AH-2	-
TB614	21	19 (0.75)	130.0 (5.12)	1112 (250)	-40 (-40)	150 (302)	Yes	AH-2	-
TB615	21	19 (0.75)	180.3 (7.10)	1112 (250)	-40 (-40)	150 (302)	Yes	AH-2	-
TB711	21	19 (0.75)	33.0 (1.30)	1112 (250)	-40 (-40)	150 (302)	Yes	AH-2	-
TB712	21	19 (0.75)	55.9 (2.20)	1112 (250)	-40 (-40)	150 (302)	Yes	AH-2	-
TB713	21	19 (0.75)	81.3 (3.20)	1112 (250)	-40 (-40)	150 (302)	Yes	AH-2	-
TB714	21	19 (0.75)	130.0 (5.12)	1112 (250)	-40 (-40)	150 (302)	Yes	AH-2	-
TB715	21	19 (0.75)	180.3 (7.10)	1112 (250)	-40 (-40)	150 (302)	Yes	AH-2	-

Multi-Lok Un-Coated Metallic Cable Ties Investigated to ANSI/UL 62275

Cat. No.	Type Dsg.	Bundle Diam., mm(in.)		Loop Tensile Str., N(lbf)	Operating Temp., °C(°F)		Resistant to UV Light	Plenum Rating	Also Classified to [^] IEC 62275 and EN 62275
		Min	Max		Min	Max			
AE601	2	19 (0.75)	33 (1.30)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	
AE602	2	19 (0.75)	56 (2.20)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-

[Learn More](#)

AE603	2	19 (0.75)	81 (3.19)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
AE604	2	19 (0.75)	130 (5.12)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
AE605	2	19 (0.75)	180 (7.09)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
AE701	2	19 (0.75)	33 (1.30)	1846 (415)	-60 (-76)	300 (572)	Yes	AH-1	-
AE702	2	19 (0.75)	56 (2.20)	1846 (415)	-60 (-76)	300 (572)	Yes	AH-1	-
AE703	2	19 (0.75)	81 (3.19)	1846 (415)	-60 (-76)	300 (572)	Yes	AH-1	-
AE704	2	19 (0.75)	130 (5.12)	1846 (415)	-60 (-76)	300 (572)	Yes	AH-1	-
AE705	2	19 (0.75)	180 (7.09)	1846 (415)	-60 (-76)	300 (572)	Yes	AH-1	-
AM601	2	19 (0.75)	33 (1.30)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
AM602	2	19 (0.75)	56 (2.20)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
AM603	2	19 (0.75)	81 (3.19)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
AM604	2	19 (0.75)	130 (5.12)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
AM605	2	19 (0.75)	180 (7.09)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
AM701	2	19 (0.75)	33 (1.30)	1846 (415)	-60 (-76)	300 (572)	Yes	AH-1	-
AM702	2	19 (0.75)	56 (2.20)	1846 (415)	-60 (-76)	300 (572)	Yes	AH-1	-
AM703	2	19 (0.75)	81 (3.19)	1846 (415)	-60 (-76)	300 (572)	Yes	AH-1	-
AM704	2	19 (0.75)	130 (5.12)	1846 (415)	-60 (-76)	300 (572)	Yes	AH-1	-
AM705	2	19 (0.75)	180 (7.09)	1846 (415)	-60 (-76)	300 (572)	Yes	AH-1	-
TB601	2	19 (0.75)	33 (1.30)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
TB602	2	19 (0.75)	56 (2.20)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
TB603	2	19 (0.75)	81 (3.19)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	
TB604	2	19 (0.75)	130 (5.12)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-

[Learn More](#)

TB605	2	19 (0.75)	180 (7.09)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
TB701	2	19 (0.75)	33 (1.30)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
TB702	2	19 (0.75)	56 (2.20)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
TB703	2	19 (0.75)	81 (3.19)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
TB704	2	19 (0.75)	130 (5.12)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
TB705	2	19 (0.75)	180 (7.09)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-

Nylon Coated-Metallic Cable Ties Investigated to ANSI/UL 62275

Cat. No.	Type Dsg.	Bundle Diam., mm(in.)		Loop Tensile Str., N(lbf)	Operating Temp., °C(°F)		Resistant to UV Light	Plenum Rating	Also Classified to [^] IEC 62275 and EN 62275
		Min	Max		Min	Max			
KE06AA	21	20 (0.79)	30-254 (1.18)	444 (100)	-40 (-40)	140 (284)	Yes	AH-2	-
KE08AA	21	20 (0.79)	30-254 (1.18)	533 (120)	-40 (-40)	140 (284)	Yes	AH-2	-

S.I.D. Tie-Lok Un-Coated Metallic Cable Ties Investigated to ANSI/UL 62275

Cat. No.	Type Dsg.	Bundle Diam., mm(in.)		Loop Tensile Str., N(lbf)	Operating Temp., °C(°F)		Resistant to UV Light	Plenum Rating	Also Classified to [^] IEC 62275 and EN 62275
		Min	Max		Min	Max			
AM211	2	12.7 (0.50)	50.8 (2.00)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
AM212	2	12.7 (0.50)	102 (4.02)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
AM213	2	12.7 (0.50)	152 (5.98)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
AM214	2	12.7 (0.50)	203 (7.99)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
AM215	2	12.7 (0.50)	254 (10.00)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
AS211	2	12.7 (0.50)	50.8 (2.00)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
AS212	2	12.7 (0.50)	102 (4.02)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-

[. Learn More](#)

AS213	2	12.7 (0.50)	152 (5.98)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
AS214	2	12.7 (0.50)	203 (7.99)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
AS215	2	12.7 (0.50)	254 (10.00)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
AS221	2	12.7 (0.50)	25.4 (1.00)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1	-
AS222	2	12.7 (0.50)	50.8 (2.00)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1	-
AS223	2	12.7 (0.50)	102 (4.02)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1	-
AS224	2	12.7 (0.50)	152 (5.98)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1	-
AS225	2	12.7 (0.50)	203 (7.99)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1	-
AS411	2	12.7 (0.50)	50.8 (2.00)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
AS412	2	12.7 (0.50)	102 (4.02)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
AS413	2	12.7 (0.50)	152 (5.98)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
AS414	2	12.7 (0.50)	203 (7.99)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
AS415	2	12.7 (0.50)	254 (10.00)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1	-
AS421	2	12.7 (0.50)	25.4 (1.00)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1	-
AS422	2	12.7 (0.50)	50.8 (2.00)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1	-
AS423	2	12.7 (0.50)	102 (4.02)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1	-
AS424	2	12.7 (0.50)	152 (5.98)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1	-
AS425	2	12.7 (0.50)	203 (7.99)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1	-

Un-Coated Metallic Cable Ties Investigated to ANSI/UL 62275

Cat. No.	Type Dsg.	Bundle Diam., mm(in.)		Loop Tensile Str., N(lbf)	Operating Temp., °C(°F)		Resistant to UV Light	Plenum Rating	Also Classified to [^]
		Min	Max		Min	Max			
KE01AAUK	2	20 (0.79)	30-305 (1.18)	890 (200)	-60 (-76)	300 (572)	Yes	AH-1	-

[Learn More](#)

KE03AAUK	2	20 (0.79)	30-305 (1.18)	1334 (300)	-60 (-76)	300 (572)	Yes	AH-1	-
KE11AAUK	2	20 (0.79)	30-305 (1.18)	890 (200)	-60 (-76)	300 (572)	Yes	AH-1	-
KE13AAUK	2	20 (0.79)	30-338 (1.18)	1334 (300)	-60 (-76)	300 (572)	Yes	AH-1	-
XE01AAUK	2	20 (0.79)	30-305 (1.18)	890 (200)	-60 (-76)	300 (572)	Yes	AH-1	-
XE03AAUK	2	20 (0.79)	30-305 (1.18)	1334 (300)	-60 (-76)	300 (572)	Yes	AH-1	-
XE11AAUK	2	20 (0.79)	30-305 (1.18)	890 (200)	-60 (-76)	300 (572)	Yes	AH-1	-
XE13AAUK	2	20 (0.79)	30-338 (1.18)	1334 (300)	-60 (-76)	300 (572)	Yes	AH-1	-

+ - Optionally prefixed by T as related to packing requirements and a numeric suffix related to packaging quantity.

Note - All cable ties designations may include an alphanumeric suffix related to packaging requirements and quantity.

Last Updated on 2018-03-06

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"



[. Learn More](#)