

BAND-IT

THE ULTIMATE FASTENING SYSTEMS

ULTRA-LOK® BANDING SYSTEM

Designed for quick installation, ULTRA-LOK clamps have the highest clamping force with a gap-free inside diameter. The best choice for demanding applications, ULTRA-LOK clamps are available in a free-end band & buckle or preformed clamp configuration.

- Complete Clamping Solution: Bands and install tool are engineered to work together to form a strong, consistent, permanent joint
- Nationwide distribution network with trained staff and quick shipping, plus the support of BAND-IT Engineering for custom projects.
- Steel and manufacturing process are inspected and held to the stringent automotive industry standards (IATF 16949).
- Made in the USA with USA Steel

With over 80 years of band fastening experience, and 20 years of proven results with ULTRA-LOK, BAND-IT is the trusted source for engineered fastening solutions.



The UL4000-D cordless tool uses pre-set tension settings with ULTRA-LOK bands to consistently achieve maximum clamping strength.



Preformed ULTRA-LOK bands

PRODUCT APPLICATIONS



HOSE ATTACHMENT

Ultra-Lok clamps and tools are perfect solution for joining or repairing hose fittings in the field. The Ultra-Lok system installs 3-5x faster than assemblies with hand tools, making it ideal for any hose clamping application.



TRAFFIC SIGN MOUNTING

Ultra-Lok's full tension lock provides a clamp that's 20% stronger than traditional band & buckle assemblies, making it ideal for sign hanging and traffic management applications where withstanding wind, vibration, and harsh conditions is crucial.

ULTRA-LOK® Band

| Part No. | Material | Width | | Length | | Single Wrap | | Double Wrap | | Package Quantity | Weight | |
|---------------------------|----------|-------|------|--------|------|-------------|------|---------------|-----|------------------|--------|-----|
| | | in | mm | in | mm | in | mm | in | mm | | lbs | kg |
| Ultra-Lok® Band | | | | | | | | | | | | |
| UL1018** | 201 SS | .5 | 12.7 | 18 | 457 | 3 | 76 | not suggested | | 50/Box | 4.1 | 1.9 |
| UL1024** | 201 SS | .5 | 12.7 | 24 | 610 | 5 | 127 | 2.5 | 64 | 50/Box | 5.3 | 2.4 |
| UL1028** | 201 SS | .5 | 12.7 | 28 | 711 | 6 | 152 | 3.0 | 76 | 50/Box | 6.4 | 0.9 |
| UL1032** | 201 SS | .5 | 12.7 | 32 | 813 | 7 | 178 | 3.5 | 89 | 50/Box | 7.2 | 3.3 |
| UL1036** | 201 SS | .5 | 12.7 | 36 | 914 | 8 | 203 | 4.0 | 102 | 50/Box | 8.0 | 3.6 |
| UL1046** | 201 SS | .5 | 12.7 | 46 | 1168 | 11 | 280 | 5.5 | 140 | 25/Box | 5.9 | 2.7 |
| UL1056** | 201 SS | .5 | 12.7 | 56 | 1422 | 14 | 356 | 7.0 | 178 | 25/Box | 7.1 | 3.2 |
| UL1070** | 201 SS | .5 | 12.7 | 70 | 1778 | 18 | 457 | 9.0 | 229 | 25/Box | 8.5 | 3.9 |
| UL1086** | 201 SS | .5 | 12.7 | 86 | 2184 | 22 | 559 | 11.0 | 280 | 25/Box | 10.2 | 4.6 |
| UL1096** | 201 SS | .5 | 12.7 | 96 | 2438 | 25 | 635 | 12.5 | 318 | 25/Box | 11.2 | 5.1 |
| UL1106** | 201 SS | .5 | 12.7 | 106 | 2692 | 28 | 711 | 14.0 | 356 | 25/Box | 12.3 | 5.6 |
| UL1116** | 201 SS | .5 | 12.7 | 116 | 2946 | 31 | 787 | 15.5 | 394 | 25/Box | 13.3 | 6.0 |
| UL2020 | 201 SS | .75 | 19.1 | 20 | 508 | 4 | 102 | not suggested | | 30/Tote | 4.3 | 2.0 |
| UL2024 | 201 SS | .75 | 19.1 | 24 | 610 | 5 | 127 | not suggested | | 25/Tote | 4.1 | 1.9 |
| UL2028 | 201 SS | .75 | 19.1 | 28 | 711 | 6 | 152 | not suggested | | 21/Tote | 4.3 | 2.0 |
| UL2032 | 201 SS | .75 | 19.1 | 32 | 813 | 7 | 178 | 3.5 | 89 | 19/Tote | 4.3 | 2.0 |
| UL2036 | 201 SS | .75 | 19.1 | 36 | 914 | 8 | 252 | 4.0 | 102 | 33/Tote | 8.2 | 3.7 |
| UL2040 | 201 SS | .75 | 19.1 | 40 | 1016 | 10 | 254 | 4.5 | 127 | 30/Tote | 7.75 | 3.5 |
| UL2044 | 201 SS | .75 | 19.1 | 44 | 1118 | 11 | 267 | 5.5 | 140 | 27/Tote | 8.2 | 3.7 |
| UL2048 | 201 SS | .75 | 19.1 | 48 | 1219 | 12 | 305 | 6.0 | 153 | 25/Tote | 8.2 | 3.7 |
| UL2052 | 201 SS | .75 | 19.1 | 52 | 1321 | 13 | 330 | 6.5 | 165 | 23/Tote | 8.2 | 3.7 |
| UL2060 | 201 SS | .75 | 19.1 | 60 | 1524 | 15 | 381 | 7.5 | 191 | 20/Tote | 8.2 | 3.7 |
| UL2068 | 201 SS | .75 | 19.1 | 68 | 1727 | 17 | 445 | 8.5 | 216 | 17/Tote | 8.2 | 3.7 |
| UL2076 | 201 SS | .75 | 19.1 | 76 | 1930 | 20 | 508 | 10.0 | 254 | 15/Tote | 8.2 | 3.7 |
| UL2084 | 201 SS | .75 | 19.1 | 84 | 2134 | 22 | 559 | 11.0 | 280 | 14/Tote | 8.2 | 3.7 |
| UL2092 | 201 SS | .75 | 19.1 | 92 | 2337 | 24 | 622 | 12.0 | 305 | 13/Tote | 8.2 | 3.7 |
| UL2120 | 201 SS | .75 | 19.1 | 120 | 3048 | 32 | 826 | 16.0 | 407 | 10/Tote | 8.2 | 3.7 |
| UL2150 | 201 SS | .75 | 19.1 | 150 | 3810 | 41 | 1029 | 20.5 | 508 | 8/Tote | 8.2 | 3.7 |
| UL2175 | 201 SS | .75 | 19.1 | 175 | 4445 | 48 | 1232 | 24.0 | 610 | 7/Tote | 8.2 | 3.7 |
| Ultra-Lok® Buckles | | | | | | | | | | | | |
| UB2549 | 201 SS | | | | | | | | | 100/Box | 3.7 | 1.7 |
| UB2569 | 201 SS | | | | | | | | | 100/Box | 3.7 | 1.7 |

** 1/2" Bands will require M09387 for UL4000 and UL9010 Tool.

3/4" width band lengths 36" or longer in 100' Totes; 34" or less in 50' Totes.



Bands



Buckles

ULTRA-LOK® Preformed Clamps

| Part No. | Material | Width | | Thickness | | Inside Diameter | | Package Weight | | Package Quantity |
|-----------------------------------|-----------------|-------|------|-----------|------|-----------------|-----|----------------|------|------------------|
| | | In | mm | In | mm | In | mm | Lbs | Kg | |
| Ultra-Lok® Preformed Clamp | | | | | | | | | | |
| UL2799** | 201 SS 1/4 Hard | 0.5 | 12.7 | 0.030 | 0.76 | 1.5 | 38 | 9.1 | 4.1 | 100/Box |
| UL2839** | 201 SS 1/4 Hard | 0.5 | 12.7 | 0.030 | 0.76 | 2.0 | 50 | 10.6 | 4.8 | 100/Box |
| UL2869** | 201 SS 1/4 Hard | 0.5 | 12.7 | 0.030 | 0.76 | 2.75 | 69 | 12.7 | 5.8 | 100/Box |
| UL2919** | 201 SS 1/4 Hard | 0.5 | 12.7 | 0.030 | 0.76 | 4.0 | 101 | 16.7 | 7.6 | 100/Box |
| UL2279 | 201 SS 1/4 Hard | 0.75 | 19.1 | 0.030 | 0.76 | 2.0 | 50 | 14.9 | 6.8 | 100/Box |
| UL2109 | 201 SS 1/4 Hard | 0.75 | 19.1 | 0.030 | 0.76 | 2.75 | 69 | 9.2 | 4.2 | 50/Box |
| UL2119 | 201 SS 1/4 Hard | 0.75 | 19.1 | 0.030 | 0.76 | 3.0 | 76 | 10.4 | 4.7 | 50/Box |
| UL2129 | 201 SS 1/4 Hard | 0.75 | 19.1 | 0.030 | 0.76 | 3.5 | 88 | 10.8 | 4.9 | 50/Box |
| UL2139 | 201 SS 1/4 Hard | 0.75 | 19.1 | 0.030 | 0.76 | 4.0 | 101 | 6.4 | 2.9 | 25/Box |
| UL2149 | 201 SS 1/4 Hard | 0.75 | 19.1 | 0.030 | 0.76 | 4.5 | 114 | 7.0 | 3.2 | 25/Box |
| UL2159 | 201 SS 1/4 Hard | 0.75 | 19.1 | 0.030 | 0.76 | 5.0 | 127 | 7.5 | 3.4 | 25/Box |
| UL2709 | 201 SS 1/4 Hard | 0.75 | 19.1 | 0.030 | 0.76 | 5.25 | 139 | 7.3 | 3.3 | 25/Box |
| UL2169 | 201 SS 1/4 Hard | 0.75 | 19.1 | 0.030 | 0.76 | 6.0 | 152 | 8.4 | 3.8 | 25/Box |
| UL2179 | 201 SS 1/4 Hard | 0.75 | 19.1 | 0.030 | 0.76 | 6.5 | 165 | 10.2 | 4.6 | 25/Box |
| UL2189 | 201 SS 1/4 Hard | 0.75 | 19.1 | 0.030 | 0.76 | 7.0 | 177 | 9.8 | 4.4 | 25/Box |
| UL2199 | 201 SS 1/4 Hard | 0.75 | 19.1 | 0.030 | 0.76 | 8.0 | 203 | 11.0 | 5.0 | 25/Box |
| UL2289 | 201 SS 1/4 Hard | 0.75 | 19.1 | 0.030 | 0.76 | 9.0 | 228 | 5.1 | 2.31 | 10/Box |

**1/2" bands require M09387 for UL4000 or UL9010 tools.

Preformed Clamps

